




## **TECHNICAL DATA SHEET**





## Zinc Stearate Release Aerosol 41012N

**Product Description** A dry, light, water-repellent powder, Zinc Stearate is

economical to use and gives better finishes. Use it for polycarbonates, polypropylenes, polysulfones and rubber molding. Compatible with oil-based paints, its

formulation results in fewer rejects and lower

production costs.

Mold Release **Applications** 

**Unit Package Description** 16 ounce aerosol

**Generic Description** Mold Release

**Net Weight Fill** 11.5 net ounces

858799000103 **UPC Code** 

White Powder **Appearance** 

Odor Mild. Petroleum like

Flash Point F Not Applicable

Flash Point C Not Applicable

Zinc Stearate **Base Type** 

**Evaporation Rate** Fast

**HMIS Rating** 1, 3, 0, B

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity **DOT Proper Shipping Name** 

VOC % (Federal) 59.17

446.93 VOC g/L (Federal)

VOC lbs./Gal (Federal) 3.72

Removal Remove with organic or hydrocarbon solvents

**Units Per Case** 12

Case Weight (lbs) 13

**Working Temperature F** 32 to 600 degrees

**Working Temperature C** 0 to 315 degrees

**Propellant** DME/152A

NFPA Aerosol Flammability Level 1

info@goengineer.com 800.688.3234