## 🗇 goengineer

# **XM200G SERIES**

## PERFORMANCE METAL 3D PRINTING AT AN AFFORDABLE PRICE







3D PRINTER SALES info@goengineer.com 800.688.3234 CONSUMABLES HELP supplies@goengineer.com 855.470.0647 **3D PRINTER SUPPORT** 

AMsupport@goengineer.com 855.470.0647

### A HIGHLY CONFIGURABLE COMBINATION OF INDUSTRIAL SPEED & PERFORMANCE AT AN AFFORDABLE PRICE

Xact Metal 3D printers combine the critical additive manufacturing specifications of metal powder-bed fusion (SLM/DMLS) with cutting-edge technology to offer uncompromised as-printed part quality at an affordable price.

The XM200G printer series meets the specification demands of high-performance use cases in manufacturing, research & development and other applications where print speed, part quality, and affordable price is essential.

#### **XM200G FEATURES**

- Single or Dual laser
- > Overlapping dual-laser work-areas
- > High-speed galvanometer with water-cooled performance option
- Premium F-theta lens for optimized micron consistency across scan field
- Large build volume
- Small footprint
- Modern software architecture
- > Open material platform
- Integrated powder handling

#### **TECHNICAL SPECS**

Build Volume	150 x 150 x 150 mm (5.9 x 5.9 x 5.9 in)
Laser Type <sup>1</sup>	<ul> <li>XM200G - Single 100W, 200W, or 400W Yb fiber laser</li> <li>XM200G2 - Dual 100W, 200W, or 400W Yb fiber lasers</li> </ul>
Build Speed	<ul> <li>XM200G - ~6 to 9 cc/hr</li> <li>XM200G2 - ~12 to 16 cc/hr</li> </ul>
Jogging Speed	Up to 20.7 m/sec (Standard galvo), 34.6 m/sec (Performance galvo)
Precision Optics Spot Size	50 or 100 µm
Layer Thickness	20 up to 100 µm
Glovebox	Available
User Interface	18.5" intuitive user-friendly touch screen
Electrical <sup>2</sup>	Power Supply 100-120/200-240 VAC Single Phase, 50/60 Hz 1.5 kW, 2.0 kW Peak
Exterior Dimensions	650 x 780 x 1,930 mm³ - W x D x H (25.6 x 30.7 x 76 in³)
Weight	<ul> <li>XM200G - ~380 kgs (~840 lbs)</li> <li>XM200G2 - ~425 kgs (~940 lbs)</li> </ul>
Powder Options <sup>3</sup>	<ul> <li>Aluminum Si10Mg</li> <li>Bronze, Copper (C18150)</li> <li>Stainless Steel: 316L, 17-4 PH, 15-5, 400 Series</li> <li>Super Alloys: 718, 625, Cobalt Chrome F75, Hastelloy<sup>®</sup> X,</li> <li>Titanium Ti64</li> <li>Tooling Steels: Maraging M300</li> </ul>



Xact Metal and Xact Core are trademarks of Xact Metal, Inc.

1. Class 1 Laser Product, 2. Not all configurations available on 120 watts, 3. Availability of parameters available on request

# **ODENDINEEL**

3D PRINTER SALES info@goengineer.com 800.688.3234 CONSUMABLES HELP supplies@goengineer.com 855.470.0647 3D PRINTER SUPPORT AMsupport@goengineer.com 855.470.0647