![goengineer logo]

PostProcess™
DECI Duo™
SURFACE FINISHING

![PostProcess logo] Automated. Intelligent. Comprehensive.

HARDWARE FEATURES

- Automated turntable to fixture parts to ensure held in place during operation
- Clean In Place (CIP) system - when finishing is complete, nozzles rinse parts in the same chamber
- Hinged electrical panel design allows for easy access for maintaining controls and motor
- Fully welded stainless steel chamber provides corrosion resistance and operator safety
- Pumping system with easy maintenance
- Casters for easy installation / relocation

RESULTING IN...
+ Preserving fine feature part detail
+ Fast cycle times
+ Automated finishing

SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Proprietary Agitation Algorithms
- Variable temperature up to 130°F (54°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Media Seperation Sequence
- Pre-programmed preventative maintenance schedules

RESULTING IN...
+ Minimal operator intervention
+ Precision machine programming
+ Consistency and repeatability

PRODUCT SPECIFICATIONS

SIZE & WEIGHT SPECIFICATIONS

- **Envelope:**
  Both Nozzles: 15" L x 15" W x 12" H
  (38 cm x 38 cm x 30.4 cm)
  Top Nozzle Only: 15" L x 15" W x 15" H
  (38 cm x 38 cm x 38 cm)
- **Machine Footprint (Chamber Door Closed):**
  69.5" L × 37" W × 94" H
  (177 cm x 94 cm x 239 cm)
  Machine Footprint (Chamber Door Open):
  69.5" L × 67" W × 94" H
  (177 cm x 170 cm x 239 cm)
- **Approx. Weight**: 2180 lbs. (989 kg) empty;
  2350 lbs. (1066 kg) full

ELECTRICAL SPECIFICATIONS

- Voltage: 480V 3 Phase
- Amperage: 25A
- Connector: HBLS430C7W
  **other voltage options available

CONSUMABLES

- PLM-001-DUO detergent
- ZB-CBM, MB-CBM, ZS-CBM425, AS-ALO and PS-SS suspended solids

SAFETY FEATURES

- Emergency stop
- External LED lighted chamber
- Sealed chamber with door safety lock
- Compliant with all OSHA regulations
- CE

MATERIALS AND TECHNOLOGIES

DMLS · SLM · DED